









# mini lime®

#### **CONDENSATE REMOVAL PUMP**

The patented Lime System is a unique one piece elbow pump, mounted within a dedicated trunking system. It's compact design allows easy install & maintenance. ('Pump only pack' also available).



12L/h max. flow



10m max. rec. head (flow rate 6L/h)



23dB(A)



- One piece pump
- Left or right install
- Trunking system options
- Easy access for servicing


## **SUITABILITY**






✓ Perfect for...

Commercial use eg. offices, restaurants







MINI LIME SPECIFICATIONS		
Max. flow	12L/h @ 0 head	
Max. rec. head	10m	
Max. suction lift	n/a	
Sound level@1m	23dB(A)	
Power supply	230V AC 50-60Hz 0.1A*	
Rated	Non continuous	
Class	II appliance 🔲	
Max. unit output	16kW / 54,000Btu/h	
Max. water temp	40°C / 104°F	
Discharge tube	6mm ID	
IP Protection	IPX4	
Safety Switch	3.0A Normally closed	
Thermal protection	✓	
Fully potted	✓	
Self priming	✓	

MINI LIME SYSTEM OPTIONS			
System	Colour	Part No.	
Slimline + 80mm -	Ivory	FP1500	
50mm	O White	FP2857	
BBJ (Aerco)	lvory	FP2083	
65mm ↓	O White	FP2856	
Inoac +80mm	O Ivory	FP2100	
50mm ↓	O White	FP2855	
Artiplastic 79mm 79mm	O Ivory	FP2077	
Mini Lime Replacement	FP2124/3		
Mini Lime 'Extra' Replac (Export only)	FP2124		
* Other voltages available			

#### SUGGESTED XTRA ACCESSORIES System Part No. FP2620 1 Amp Fuse Tube To Soil Stack FP2038 Adaptor Vinyl Tube Braided AX5100 1/4" (6mm)

For more installation accessories take a look at our Aspen Xtra range

## IN THE BOX

Mini Lime pump (including 300mm 6mm ID discharge tube with connector and 1.5m hard wired power cable) • 220mm Lime green inlet hose 14mm ID • 150mm Vinyl breather tube 6mm ID • Anti siphon device • Elbow front and back • 800mm Conduit front and back

- Internal conduit sleeve (Slimline system only)
- Gasket (Slimline, BBJ and Inoac/Inaba systems only) • Ceiling plate • Drain connector kit
- Fixing kit Install manual
- Download manual at aspenpumps.com
- View install video at aspenpumps.com









† Pump only – no trunking included



