


T-Fresh Floor Standing Heat Pumps

Find out more at www.greeac.co.nz

Gree T-Fresh Floor Standing Heat Pumps

Side-drawing filter design for convenient cleaning*

The filter adopts user-friendly side-drawing design, which is more convenient for cleaning.



Fully-closed air outlet

The air outlet can be completely closed to avoid dust from entering, safeguarding the health of your family.



Туре		T-Fresh
Model	Ind	GVH32ALXH-K6DNC7A/I
	Out	GVH32ALXH-K6DNB2A/O
Performance		
Cooling Capacity (Range)	kW	10.0
Heating Capacity (Range)	kW	10.3
Cooling Power Input	kW	2.73
Heating Power Input	kW	3.02
Cooling EER	w/w	3.66
Heating COP	w/w	3.4
Dehumidifying Volume	L/Hr	5.0
Air Flow Volume (Max)	L/Sec	361~514
Sound Pressure (Min/Max) Ind	dB(A)	47~52
Power Supply (Outdoor)	V/Hz/Ph	220~240/50/1
Recommended Circuit Breaker	А	25
Nominal Current (Cool / Heat)	А	11.5/13.5
Control Wiring		4 Core
Indoor Dimensions (WxHxD)	mm	587 x 1882 x 394
Indoor Net Weight	kg	57
Outdoor Dimensions (WxHxD)	mm	1000 x 746 x 427
Outdoor Net Weight	kg	59.5
Operating Temp Range Cool	°C	-10° ~ 50°
Operating Temp Range Heat	°C	-15° ~ 24°
Refrigerant Type		R32
Refrigerant Charge	kg	1.9
Max Pipe Length (pre-charged)	М	25 (10)
Max height		10
Additional Refrigerant	g/m	40
Pipe Connection		1/4" ~ 5/8"

Features



Standard

Gree continues to work to improve their air conditioners. To that effect the specifications are subject to change without notice. All Gree air conditioners sold in New Zealand are registered for MEPS and comply with AS/NZS 3823, including the 2019 GEMS determination. Furthermore all Gree air conditioners comply with AS/NZS 60335-2-40 electrical safety and carry the RCM mark under AS/NZS 4417. A Suppliers Declaration of Conformity (SDoC) is available on request.

Optional