

Section 1 Identification of Chemical Product and Company

Code	Description	Size	Colour
20600	Gorilla MS Sealant	425 g	White
20601	Gorilla MS Sealant	425 g	Grey
20602	Gorilla MS Sealant	415 g	Black
20603	Gorilla MS Sealant	600 ml	Black
20604	Gorilla MS Sealant	600 ml	Grey
20605	Gorilla MS Sealant	600 ml	White
20607	Gorilla MS Sealant	600 ml	Titania

Recommended use:	Sealant	
HSNO Group Standard	HSR002670	
UN number, shipping name and packaging group:	Not regulated	
Supplier contact details:	Soudal Ltd	Freephone: 0800 70 10 80
	134 Kohia Drive	Phone: (07) 847 5540
	Horotiu	
	Hamilton 3288	Email: info@soudal.co.nz
	New Zealand	Website: www.soudal.co.nz
POISON CENTRE NUMBER: 0800 764 766 (24 hours)		

Section 2 Hazards Identification

Statement of Hazardous Nature

This product is classified as: **HAZARDOUS SUBSTANCE** according to the criteria of GHS v7.

NOT REGULATED under NZS5433:2020 Transport of Dangerous Goods on Land

GHS classification:

Classification	GHS Hazard statements
Skin Irritation Category 2	H315 Causes skin irritation
Eye Irritation Category 2	H319 Causes serious eye irritation
Skin Sensitisation Category 1	H317 May cause an allergic skin reaction
Reproductive Toxicity Category 2	H361 Suspected of damaging fertility or the unborn child

HSNO Signal Word:

WARNING



Precautionary Statements:	P102	Keep out of the reach of children
	P103	Read label before use
	P261	Avoid breathing mists/ vapours/ sprays

P280	Wear protective gloves, protective clothing, eye protection and face protection
P264	Wash all exposed external body areas thoroughly after handling
P272	Contaminated work clothing should not be allowed out of the workplace
P405	Store locked up
P501	Dispose of contents/ container to authorised hazardous or special waste collection points in accordance with local regulations.

Section 3. Composition/Information on Ingredients

Ingredient	CAS No.	Individual GHS classification	Concentration (% by Wt.)
Diundecyl phthalate	85507-79-5	Skin Irritation Category 2	10 - 20
N,N'-ethylenebisstearamide	110-30-5	Skin Irritation Category 2 Eye Irritation Category 2 STOT - SE RTI Category 3	< 1
Trimethoxyvinyl silane	2768-02-7	Flammable Liquid Category 2 Acute Inhalation Toxicity Category 4	< 1
3-aminopropyltrimethoxysilane	13822-56-5	Skin Irritation Category 2 Eye Irritation Category 2	< 1
Distillates (Fisher Tropisch), heavy, C18-50 branched, cyclic and linear	848301-69-9	Skin Irritation Category 2 Aspiration Category 1 Chronic Aquatic Hazard Category 2	< 1
Diocetyl tinbis(acetylacetonate)	54068-28-9	Skin Sensitisation Category 1 Reproductive Toxicity Category 1 STOT - RE Category 2 Chronic Aquatic Hazard Category 3	< 1
Bumetrizole	3896-11-5	Eye Irritation Category 2 Skin Sensitisation Category 1 Chronic Aquatic Hazard Category 3	< 1
UV Inhibitor	52829-07-9	Eye Irritation Category 2 Chronic Aquatic Hazard Category 2	< 1
Ingredients not contributing to classification			balance

This is a commercial product whose exact ratio of components may vary slightly. Minor quantities of other non-hazardous ingredients are also possible.

Section 4 First Aid Measures

NZ Poisons Centre 0800 POISON (0800 764 766) | NZ Emergency Services: 111

Eye contact:

Immediately hold eyelids apart and flush the eye continuously with running water. Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes. Transport to hospital or doctor without delay. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

Skin contact:

Immediately remove all contaminated clothing, including footwear. Flush skin and hair with running water (and soap if available). Seek medical attention in event of irritation.

Inhalation:

Remove from contaminated area. Lay patient down. Keep warm and rested. Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. Transport to hospital, or doctor, without delay

Ingestion:

Immediately give a glass of water. First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

General advice and advice for physicians:

Treat symptomatically

Section 5 Fire-Fighting Measures**Extinguishing media:**

Foam. Dry chemical powder. Carbon dioxide. Water spray or fog - Large fires only.

Fire/ Explosion Hazard:

Combustible. Will burn if ignited.

Advice for fire-fighters:

Alert Fire Brigade and tell them location and nature of hazard. Wear breathing apparatus plus protective gloves. Prevent, by any means available, spillage from entering drains or water courses. Use water delivered as a fine spray to control fire and cool adjacent area. DO NOT approach containers suspected to be hot. Cool fire exposed containers with water spray from a protected location. If safe to do so, remove containers from path of fire. Equipment should be thoroughly decontaminated after use.

Section 6 Accidental Release Measures**Minor Spills:**

Environmental hazard - contain spillage. Clean up all spills immediately. Avoid contact with skin and eyes. Wear impervious gloves and safety goggles. Trowel up/scrape up. Place spilled material in clean, dry, sealed container. Flush spill area with water.

Major Spills:

Environmental hazard - contain spillage. Minor hazard. Clear area of personnel. Alert Fire Brigade and tell them location and nature of hazard. Control personal contact with the substance, by using protective equipment as required. Prevent spillage from entering drains or water ways. Contain spill with sand, earth or vermiculite. Collect recoverable product into labelled containers for recycling. Absorb remaining product with sand, earth or vermiculite and place in appropriate containers for disposal. Wash area and prevent runoff into drains or waterways. If contamination of drains or waterways occurs, advise emergency services.

Section 7 Handling and Storage**Handling:**

Avoid all personal contact, including inhalation. Wear protective clothing when risk of exposure occurs. Use in a well-ventilated area. Prevent concentration in hollows and sumps. DO NOT enter confined spaces until atmosphere has been checked. DO NOT allow material to contact humans, exposed food or food utensils. Avoid contact with incompatible materials. When handling, DO NOT eat, drink or smoke. Keep containers securely sealed when not in use. Avoid physical damage to containers. Always wash hands with soap and water after handling. Work clothes should be laundered separately. Launder contaminated clothing before re-use. Use good occupational work practice. Observe manufacturer's storage and handling recommendations contained within this SDS. Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.

Storage:

Store in original containers. Keep containers securely sealed. Store in a cool, dry, well-ventilated area. Store away from incompatible materials and foodstuff containers. Protect containers against physical damage and check regularly for leaks. Observe manufacturer's storage and handling recommendations contained within this SDS

Suitable Container:

Packaging as recommended by manufacturer. Check all containers are clearly labelled and free from leaks.

Section 8 Exposure Controls/Personal Protection

Exposure Limits

CAS no.	Substance or ingredient	WES-TWA	WES-STEL
110-30-5	N,N'-ethylenebisstearamide	3 mg/m ³ Respirable 10 mg/m ³ inhalable	
848301-69-9	Distillates (Fisher Tropsch), heavy, C ₁₈₋₅₀ branched, cyclic and linear	5 mg/m ³ as Oil mist, mineral	
3896-11-5	Bumetrizol	3 mg/m ³ Respirable 10 mg/m ³ inhalable	
52829-07-9	UV Inhibitor	3 mg/m ³ Respirable 10 mg/m ³ inhalable	

The TWA exposure value is the average airborne concentration of a particular substance when calculated over a normal 8 hour working day for a 5-day working week. The STEL (Short Term Exposure Limit) is an exposure value that may be equalled (but should not be exceeded) for no longer than 15 minutes and should not be repeated more than 4 times per day. There should be at least 60 minutes between successive exposures at the STEL. The term "peak" is used when the TWA limit, because of the rapid action of the substance, should never be exceeded, even briefly.

Engineering Controls:

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are: Process controls which involve changing the way a job activity or process is done to reduce the risk. Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use. Employers may need to use multiple types of controls to prevent employee overexposure. General exhaust is adequate under normal operating conditions. Local exhaust ventilation may be required in specific circumstances. If risk of overexposure exists, wear approved respirator. Correct fit is essential to obtain adequate protection. Provide adequate ventilation in warehouse or closed storage areas. Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.

Exposure controls:

Control	Protective measure
Eye	Safety glasses with side shields. Chemical goggles. Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59], [AS/NZS 1336 or national equivalent]
Respiratory	Not generally required. If workplace exposure standards are likely to be exceeded, a Type A-P filter is recommended
Skin	Wear chemical protective gloves, e.g. PE/EVAL/PE. Wear safety footwear or safety gumboots, e.g. Rubber NOTE: The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact. Contaminated leather items, such as shoes, belts and watchbands should be removed and destroyed.

Section 9 Physical and Chemical Properties

General substance properties:

Property	Details
Appearance	Coloured paste
Odour	odourless

pH	Not available
Vapour pressure	Not available
Vapour Density	Not available
Viscosity	Pasty
Boiling Point	No data
Volatile materials	Not available
Freezing/melting point	Not available
Water Solubility	Immiscible
Specific gravity/density	1.45 g/ml
Flash point	Not available
Auto-ignition temperature	No data
Upper and lower flammability limits	Not available
Corrosiveness	Not available

Section 10 Stability and Reactivity

Stability:

Unstable in the presence of incompatible materials. Product is considered stable. Hazardous polymerisation will not occur.

Conditions to avoid:

Incompatible materials to avoid:

Oxidising or reducing agents

Hazardous decomposition products:

Carbon monoxide (CO) carbon dioxide (CO₂) other pyrolysis products typical of burning organic material.

Section 11 Toxicological Information

Summary of Toxicity

Test	Data and symptoms of exposure
Inhaled	The material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage. Inhalation of oil droplets or aerosols may cause discomfort and may produce chemical inflammation of the lungs.
Oral	The material has NOT been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence
Dermal	This material can cause inflammation of the skin on contact in some persons. The material may accentuate any pre-existing dermatitis condition Skin contact is not thought to have harmful health effects (as classified under EC Directives); the material may still produce health damage following entry through wounds, lesions or abrasions. Irritation and skin reactions are possible with sensitive skin Open cuts, abraded or irritated skin should not be exposed to this material Entry into the bloodstream through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.
Eye	If applied to the eyes, this material causes severe eye damage.

Chronic	Long-term exposure to respiratory irritants may result in airways disease, involving difficulty breathing and related whole-body problems. There has been concern that this material can cause cancer or mutations, but there is not enough data to make an assessment. Skin contact with the material is more likely to cause a sensitisation reaction in some persons compared to the general population. Ample evidence from experiments exists that there is a suspicion this material directly reduces fertility. Based on experience with animal studies, exposure to the material may result in toxic effects to the development of the foetus, at levels which do not cause significant toxic effects to the mother. Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure.
----------------	---

Ingredient	Oral LD ₅₀	Dermal LD ₅₀	Inhalation LC ₅₀
ATE			
Diundecyl phthalate	> 2000 mg/kg	> 2000 mg/kg	
N,N'-ethylenebisstearamide	> 2000 mg/kg	> 2000 mg/kg	
Trimethoxyvinyl silane	> 300 mg/kg	3423 mg/kg	2773 ppm/4h
3-aminopropyltrimethoxysilane	5628 mg/kg	15800 mg/kg	64000 ppm/4h
Distillates (Fisher Tropisch), heavy, C ₁₈₋₅₀ branched, cyclic and linear	> 5000 mg/kg		
Diocetyl tinbis(acetylacetonate)	2500 mg/kg	> 2000 mg/kg	1224 ppm/4h
Bumetrizole	> 2000 mg/kg	> 2000 mg/kg	> 0.27 mg/L/4h
UV Inhibitor	3700 mg/kg	>3100 mg/kg	0.5 mg/L/4h

Section 12 Ecological Information

Summary of Ecotoxicity

Do NOT allow product to come in contact with surface waters or to intertidal areas below the mean high-water mark. Do not contaminate water when cleaning equipment or disposing of equipment wash-waters. Wastes resulting from use of the product must be disposed of on site or at approved waste sites.

Ingredient	Fish	Crustacean	Algae
ATE			
Diundecyl phthalate	LC _{50 96hr} >0.78 mg/L	EC _{50 48hr} >0.02 mg/L	EC _{50 96hr} >2.1 mg/L
N,N'-ethylenebisstearamide	LC _{50 96hr} >1000 mg/L	EC _{50 48hr} >0.002 mg/L	EC _{50 72hr} >0.053 mg/L
Trimethoxyvinyl silane	LC _{50 96hr} >92.2 mg/L	EC _{50 48hr} >100 mg/L	EC _{50 72hr} >89 mg/L
3-aminopropyltrimethoxysilane	LC _{50 96hr} >100 mg/L	EC _{50 48hr} >100 mg/L	EC _{50 72hr} 603mg/L
Diocetyl tinbis(acetylacetonate)	LC _{50 96hr} >60.1 mg/L	EC _{50 48hr} >22 mg/L	EC _{50 72hr} <0.001 mg/L
Bumetrizole	LC _{50 96hr} >100 mg/L	EC _{50 48hr} >100 mg/L	EC _{50 72hr} >100mg/L
UV Inhibitor	LC _{50 96hr} 7.9 mg/L	EC _{50 48hr} 20 mg/L	EC _{50 72hr} <0.705 mg/L

Ingredient	Persistence Water/Soil	Persistence Air	Bioaccumulation	Mobility
Diundecyl phthalate	LOW	LOW	MEDIUM	LOW
N,N'-ethylenebisstearamide	HIGH	HIGH	LOW	LOW
Trimethoxyvinyl silane	HIGH	HIGH	LOW	LOW

SAFETY DATASHEET

3-aminopropyltrimethoxysilane	HIGH	HIGH	LOW	LOW
Bumetrizole	HIGH	HIGH	MEDIUM	LOW
UV Inhibitor	HIGH	HIGH	HIGH	LOW

Section 13 Disposal Considerations

Disposal methods:

Containers may still present a chemical hazard/ danger when empty. Return to supplier for reuse/ recycling if possible. Otherwise: If container cannot be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill. Where possible retain label warnings and SDS and observe all notices pertaining to the product. DO NOT recycle spilled material. Consult State Land Waste Management Authority for disposal. Neutralise spill material carefully and decontaminate empty containers and spill residues with 10% ammonia solution plus detergent or a proprietary decontaminant prior to disposal. DO NOT seal or stopper drums being decontaminated as CO₂ gas is generated and may pressurise containers. Puncture containers to prevent re-use. Bury or incinerate residues at an approved site.

Ensure that the hazardous substance is disposed in accordance with the Hazardous Substances (Disposal) Notice 2017

Packages that have been in direct contact with the hazardous substance must be only disposed if the hazardous substance was appropriately removed and cleaned out from the package. The package must be disposed according to the manufacturer's directions taking into account the material it is made of. Packages which hazardous content have been appropriately treated and removed may be recycled. The hazardous substance must only be disposed if it has been treated by a method that changed the characteristics or composition of the substance and it is no longer hazardous. Only dispose to the environment if a tolerable exposure limit has been set for the substance. Only deposit the hazardous substance into or onto a landfill or sewage facility or incinerator, where the hazardous substance can be handled and treated appropriately.

Section 14 Transport Information

NOT REGULATED

Section 15 Regulatory Information

HSNO approval number and Group Standard:

HSR002670 Surface Coatings & Colourants Subsidiary Hazard

Group Standard conditions and other regulations:

Condition	Requirement
SDS	Required
Emergency plan	Required when quantities exceed 100 Lt
Certified handler	Not required
Tracking	Not applicable
Bundling and secondary containment	Not applicable
Signage	Required when quantities exceed 100 Lt
Location Compliance certificate	Not required
Hazardous Atmosphere Zone	Not applicable
Fire extinguisher	Not applicable

National Inventories

Y = All ingredients are on the inventory

Australia AICS N

Canada	DSL	N
Canada	NDSL	N
China	IECSC	N
Europe	EINEC/ELINCS/NLP	N
Japan	ENCS	N
Korea	KECI	N
New Zealand	NZIOC	Y
Philippines	PICCS	N
USA	TSCA	N
Taiwan	TCSI	Y
Mexico	INSQ	N
Vietnam	NCI	Y
Russia	ARIPS	N

Section 16 Other Information

Revision History:

March 2023	Updated following review.
August 2018	Origination

Abbreviations:

Abbreviation	Description
CAS number	Number assigned to chemical in the Chemical Abstracts Service registry
HAZCHEM code	Code used by fire-fighters to determine correct method of action in the case of fire
HSNO	Hazardous Substances and New Organisms (Act)
ICAO Technical Instructions	International Civil Aviation Organization Technical Instructions
IMDG code	International Maritime Dangerous Goods code controlled by the International Maritime Organization (IMO)
LC ₅₀	Lethal concentration 50% - concentration fatal to 50% of the tested population
LD ₅₀	Lethal dose 50% - dose fatal to 50% of the tested population
NZS 5433:2020	New Zealand Standard 5433 (Standard for the Transport of Dangerous Goods on Land)
SDS	Safety data sheet
STEL	Short term exposure limit
TWA	Time weighted average (typically measured as 8 hours)
UN number	United nations number
WES	Workplace exposure standard

References

Chemical properties and GHS classifications derived from the New Zealand chemical classification information database (CCID). www.epa.govt.nz. Workplace exposure limits derived from Workplace Exposure Standards and Biological Exposure Indices 13th Edition (April 2022).

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material in combination with any other material or in any process, unless specified in the text.

This SDS was prepared by Collievale Enterprises in accord with the Hazardous Substances (Safety Data Sheets) Notice 2020
admin@collievale.com Phone +64 7 5432428

End of SDS